

Proportional spool valve with integrated electronics

Flange construction

- direct operated
- ◆ 0_{max} = 40 l/min
- ◆ 0_{N max} = 32 l/min
- $p_{max} = 350 \text{ bar}$

DESCRIPTION

Direct operated proportional spool valve with 4 connections in 5-chamber system with integrated electronics. The plug & play valves are factory set and adjusted and have therefore a high valve-to-valve reproducibility. With protection class IP67 for the electronics, these valves are suitable for harsh environmental conditions. Proportional to the electronically transmitted command value, the spool stroke, the spool opening and the valve volume flow increase. The control takes place via an analogue interface or a fieldbus interface (CANopen, J1939 or Profibus DP). The parameterisation takes place by means of the free of cost parameterisation and diagnostics software «PASO» or via fieldbus interface. The USB parameterisation interface is accessible through a screw plug. «PASO» is a Windows program in the flow diagram style which enables the intuitive setting and storing of all variable parameters. The data remain saved in case of a power failure and can also be reproduced and transferred to other DSVs. As an option, these valves are available with integrated controller. As feedback value generators sensors with voltage or current output can be connected directly. The available controller structures are optimised for applications with hydraulic actuations.

SYMBOL

Symmetrical control



ELECTRICAL SPECIFICATIONS

Protection class	IP67 with suitable mating connector and
	closed housing cover
Ramps	Adjustable
Parameterisation	Via fieldbus or USB
Supply voltage	12 VDC, 24 VDC

NG6 ISO 4401-03



APPLICATION

Proportional spool valves are perfectly suitable for demanding tasks due to the high resolution, large volume flow and low hysteresis. The applications are in the industry as well as in the mobile hydraulics for the smooth control of hydraulic actuators. Some examples: rotor blades control of wind generators, forestry and earth moving machines, machine tools and paper production machines with simple position control, robotics and fan control.

Meter-in control



ACTUATION

Actuation	Proportional solenoid, wet pin push
	type, pressure tight
Connection	Via device receptacle



Exact electrical specifications and detailed description of «DSV» electronics can be found on data sheet 1.13-76.



TYPE CODE

Spool valve			W	D P 	FA06 - [- [/ I	ие <u></u>	- [#	
Direct operated												
Proportional												
Flange construction												
International standard interface IS	SO, NG6											
Designation of symbols acc. to tak	ble											
Nominal volume flow rate $\mathbf{Q}_{_{N}}$	5 I/min 10 I/min	5	16 l/min 32 l/min		16 32							
Nominal voltage U _N	12 VDC 24 VDC	G12 G24										
Slip-on coil	Metal housing squ	iare										
Connection execution	Integrated electro	nics										
Hardware configuration Analog command value signal Analog command value signal CANopen according to DSP-408 Profibus DP according to Fluid Por CAN J1939 (on request)	12 pole 12 pole wer Technology	A2 A4 C1 P1 J1	7 pole 7 pole		D2 D4	(-10 . (4	10 V pr 20 mA pr	eset) eset)				
Function Amplifier Controller with current feedback v Controller with voltage feedback v	value signal (0 20 value signal (0 10	mA / 4 20 V)	mA)		R1 R2							
Sealing material	NBR FKM (Viton)				D1							
Manual override	integrated Push-button Spindle				HF1 HS1							
Design index (subject to change)												

1.10-3340

GENERAL SPECIFICATIONS

Designation	Proportional spool valve
Construction	Direct operated
Mounting	Flange construction
Nominal size	NG6 according to ISO 4401-03
Actuation	Proportional solenoid
Ambient temperature	-20+65 °C The upper temperature limit is a guideline for typical applications, in individual cases it may also be higher or lower. The electronics of the valve limit the power in case of a too high electronics temperature. More detailed information can be obtained from the operating instructions "DSV".
Weight	2,8 kg
MTTFd	150 years

HYDRAULIC SPECIFICATIONS

Working pressure	p _{max} = 350 bar
Tank pressure	p _{T max} = 160 bar
Maximum volume flow	Q _{max} = 40 l/min, see characteristics
Nominal volume flow	Q _N = 5, 10, 16, 32 l/min
Leakage oil	On request
Hysteresis	≤6 %
Fluid	Mineral oil, other fluid on request
Viscosity range	12 mm²/s320 mm²/s
Temperature range fluid	-20+70 °C
Contamination efficiency	Class 18 / 16 / 13
Filtration	Required filtration grade ß 10…16 ≥ 75, see data sheet 1.0-50



ELECTRICAL CONNECTION

X1	Analog interface (Main)		X1	Fieldbus interface (Main)
Device receptacle	M23, 12 pole male		Device receptacle	M12, 4 pole male
	1 = Supply voltage +		21	1 = Supply voltage +
⁸ 9 1 7 12 10 2	2 = Supply voltage 0 VDC		3 4	2 = Reserved for extentions
$\begin{pmatrix} & & & & & \\ & & & & & & \\ & & & & & & $	3 = Stabilised output voltage			3 = Supply voltage 0 VDC
5 4	4 = Command value signal voltage +			4 = Chassis
	5 = Command value signal voltage -			
	6 = Command value signal current +			
	7 = Command value signal current -			
	8 = Reserved for extentions			
	9 = Reserved for extentions			7

X2

V2

USB, Mini B

X1	Analog interface (Main) Connector DIN EN 175201 - 804
Device receptacle	7 pole male A = Supply voltage + B = Supply voltage 0 VDC C = Not connected D = Command value signal + E = Command value signal - F = Not connected G = Chassis
Command value signal: c when placing the order	urrent (D4) or voltage (D2) to specify

12 = Chassis

Command value signal voltage (PIN 4/5) resp. current (PIN 6/7) are selected with parameterisation and diagnostics software PASO.

10 = Enable signal (Digital input)

11 = Error signal (Digital output)

Х3	Profibus interface according to IEC 947-5-2
Device receptacle	M12, 5 pole female B-coded 1 = VP 2 = RxD / TxD - N 3 = DGND 4 = RxD / TxD - P 5 = Shield

cover Factory set

Х3	CANopen interface according to DRP 303-1
Device receptacle	M12, 5 pole male 1 = Not connected 2 = Not connected 3 = CAN Gnd 4 = CAN High 5 = CAN Low

X4 (controller only)	Feedback value interface (sensor)			
Device receptacle	M12, 5 pole female			
23	1 = Supply voltage (output) +			
$\begin{pmatrix} 5^{-5} \\ 1 & 4 \end{pmatrix}$ 2 = Feedback value signal +				
	3 = Supply voltage 0 VDC			
	4 = Not connected			
	5 = Stabilised output voltage			
Feedback value signal: current (R1) or voltage (R2) to specify				
when placing the order				

Note!

The mating connector is not included in the delivery

Parameterisation interface

Under the screw plug of the housing



PERFORMANCE SPECIFICATIONS











All values were measured over two control edges. The connections A and B were short-circuited.







FACTORY SETTINGS

Dither set for optimum hysteresis

- ◆ = Deadband: Both solenoids switched off at command value signal -2%... 2%
- = Opening pressure at command value signal + / 4%
- \blacksquare = Flow at Δp = 10 bar over two control edges + / 70% command value signal



DIMENSIONS

With analog interface, 12 pole connector

Amplifier and controller



With fieldbus interface

Amplifier



PARTS LIST

Position	Article	Description
20	223.1317	Dummy plug M16 x 1,5
21	160.6131	0-ring ID 13,00 x 1,5 (FKM)
25	062.0102	Cover
30	072.0021	Gasket 33,2 x 59,9 x 2
40	208.0100	Socket head screw M4 x 10
50	160.2093 160.6092	O-ring ID 9,25 x 1,78 (NBR) O-ring ID 9,25 x 1,78 (FKM)
60	160.2222	O-ring ID 22,22 x 2,62 (NBR)
70	154.2701	Knurled nut M23 x 1,5 x 19,7
80	253.7004	Push-button
90	253.7002	Spindle

With analog interface, 7 pole connector Amplifier and controller



- * For amplifier
- ** For controller
- *** Only controller

With fieldbus interface

Controller



HYDRAULIC CONNECTION





COMMISSIONING

For DSV amplifiers as a rule no parameter adjustments by the cusotmer are required. The plugs have to be connected in accordance with the chapter «Electrical connection».

Controllers are supplied configured as amplifiers. The adjustment of the mode of control and of the controller are carried out by the customer by means of the software adjustment (USB interface, Mini B). Further information can be found on: «www.wandfluh.com». Free- of charge download of the «PASO» software and the operation instructions for «DSV» hydraulic valves as well as the operation instructions CANopen Protocol resp. Profibus DP Protocol, with Device Profile DSP-408 for «DSV».



The mating connectors and the parameterisation cable are not part of the delivery. Refer to chapter «Accesso-ries».

SEALING MATERIAL

NBR or FKM (Viton) as standard, choice in the type code

SURFACE TREATMENT

- The valve body is painted with a two component paint
- The slip-on coil and the armature tube are zinc nickel coated
- The electronics housing / chassis is made of aluminium

INSTALLATION NOTES

Mounting type	Flange mounting 4 fixing holes for socket head screws M5 x 50
Mounting position	Any, preferably horizontal
Tightening torque	Fixing screws M _p = 5,2 Nm (screw quality 8.8, zinc coated) M _p = 5 Nm knurled nut



The length of the fixing screw depends on the base material of the connection element.

ACCESSORIES

Parameterisation software	See start-up	
Parameterisation cable for interface USB	Article no. 219.2896	
(from plug type A on Mini B, 3 m)		
Mating connector (plug female) for analog interface		
straight, soldering contact M23, 12 pole	Article no. 219.2330	
angled, soldering contact M23, 12 pole	Article no. 219.2331	
straight, soldering contact, 7 pole	Article no. 219.2335	
Threaded subplates	Data sheet 2.9-30	
Multi-station subplates	Data sheet 2.9-60	
Horizontal mounting blocks	Data sheet 2.9-100	
Technical explanations	Data sheet 1.0-100	
Hydraulic fluids	Data sheet 1.0-50	
Filtration	Data sheet 1.0-50	
Relative duty factor	Data sheet 1.1-430	



Auxiliary conditions for the cable: - External diameter 9...10.5 mm

- External diameter 9...10,5 mm
 Wire cross section max, 1 mm²
- Recommended wire cross section:
- 0...25 m = 0,75 mm² (AWG18)
- $25...50 \text{ m} = 1 \text{ mm}^2 \text{ (AWG17)}$

STANDARDS

CANopen	DRP 303-1
Profibus DP	IEC 947-5-2
Mounting interface	ISO 4401-03
Protection class	EN 60 529
Contamination efficiency	ISO 4406

MANUAL OVERRIDE

- Integrated (-) Actuation pin integrated in the armature tube. Actuation by pressing the pin
- Push-button (HF1) Integrated in the knurled nut. Actuation by pressing the push-button
- Spindle (HS1) Integrated in the knurled nut. Actuation by turning the spindle (continuously variable valve actuation)

Attention! The actuation of the manual override is possible up to a



tank pressure of: 160 bar Integrated (–) 160 bar Push-button (HF1) 250 bar Spindle (HS1)

Wandfluh AG Postfach CH-3714 Frutigen Tel. +41 33 672 72 72 Fax +41 33 672 72 12 sales@wandfluh.com