


**Proportional 2-way flow control valve
Screw-in cartridge**

- Direct operated, pressure compensated
- $Q_{max} = 25 \text{ l/min}$, $p_{max} = 350 \text{ bar}$
- $Q_{Nmax} = 25 \text{ l/min}$

M22x1,5
 ISO 7789

DESCRIPTION

Direct operated, pressure compensated proportional flow control valve, as a screw-in cartridge with a thread M33x2 for cavity acc. to ISO 7789. Four flow ranges are available. The volume flow is adjusted by a Wandfluh proportional solenoid (VDE standard 0580). The cartridge body is made of steel. A special surface treatment guarantees a good protection against corrosion and wear as well as very good low-friction characteristics of the pressure compensating- and throttle spool. The solenoid coil is zinc-/nickel-coated.

FUNCTION

The 2-way flow control valve with following pressure compensation (secondary controller) serves for maintaining the speed of a consumer constant independent of the load. The power controlled, proportional solenoid running in oil acts directly on the throttle spool, which opens the throttle segments in the cartridge body. Proportional to the current demand of the proportional solenoid, the throttle aperture changes, and with this the volume flow. In case of pressure fluctuations, the flow cross-section in the pressure compensation spool changes in such a manner, that the pressure difference in the measuring diaphragm is maintained constant. In case of a current-free solenoid, the throttle spool is held in closed position by a spring. For driving the valve, Wandfluh proportional amplifiers are available (see Register 1.13).

APPLICATION

Proportional flow control valves are suitable for feed control systems, where the consumer flow has to be maintained constant with a changing load. The screw-in cartridge is suitable for installation in control blocs as well as in flange- and sandwich valves of the NG4 and NG6 ranges. Cavity tools are available for machining the cartridge cavities in steel and aluminium (for hire or for purchase). Please refer to the data sheets in Reg. 2.13 of our documentation.


TYPE CODE

		Q N P PM22 - <input type="checkbox"/> - <input type="checkbox"/> / <input type="checkbox"/> <input type="checkbox"/> - <input type="checkbox"/> <input type="checkbox"/> # <input type="checkbox"/>	
Flow control valve			
Normally closed			
Proportional			
Screw-in cartridge M22x1,5			
Nominal volume flow rates Q_N	3,2 l/min <input type="checkbox"/> 3,2 8 l/min <input type="checkbox"/> 8 16 l/min <input type="checkbox"/> 16 25 l/min <input type="checkbox"/> 25		
Standard nominal voltage U_N	12 VDC <input type="checkbox"/> G12 24 VDC <input type="checkbox"/> G24 without solenoid coil <input type="checkbox"/> X5		
Slip-on coil	Metal housing, round <input type="checkbox"/> W Metal housing, square <input type="checkbox"/> M*		
Electric connection	Connector socket EN 175301-803 / ISO 4400 <input type="checkbox"/> D Connector socket AMP Junior-Timer <input type="checkbox"/> J Connector Deutsch DT04-2P <input type="checkbox"/> G		
Sealing material	NBR <input type="checkbox"/> FKM (Viton) <input type="checkbox"/> D1		
Manual override	Armature tube closed (standard) <input type="checkbox"/> With screwed sealing plug <input type="checkbox"/> HB0 With manual emergency actuation <input type="checkbox"/> HB4.5		
Design-Index (Subject to change)			


* Only available in conjunction with other nominal voltages and connection versions. (See data sheet 1.1-174)

SYMBOLS

simplified



detailed


GENERAL SPECIFICATIONS

Description	2-way proportional flow control valve
Construction	Screw-in cartridge for cavity acc. ISO 7789
Operations	Proportional solenoid
Mounting	Screw-in thread M22x1,5
Ambient temperature	-20...50 °C
Mounting position	any
Fastening torque	$M_D = 50 \text{ Nm}$ for screw-in cartridge $M_D = 5 \text{ Nm}$ for knurled nut
Weight	$m = 0,64 \text{ kg}$
Flow direction	1 → 2

ELECTRICAL SPECIFICATIONS

Construction	Proportional solenoid, wet pin push type, pressure tight	
Standard nominal voltage	U = 12 VDC	U = 24 VDC
Limiting current	I _G = 1360 mA	I _G = 680 mA
Relative duty factor	100 % ED (see data sheet 1.1-430)	
Protection class acc. to EN 60 529	Connection version D: IP65 J: IP66 G: IP67 and 69K	

For further electrical specifications see data sheet 1.1-173 (W)
1.1-174 (M)


HYDRAULIC SPECIFICATIONS

Fluid	Mineral oil, other fluid on request
Contamination efficiency	ISO 4406:1999, class 18/16/13 (Recommended filtration grade β _{6...10} ≥ 75) see data sheet 1.0-50/2
Viscosity range	12 mm ² /s...320 mm ² /s
Fluid temperature	-20...+70 °C
Peak pressure	p _{max} = 350 bar
Nominal volume flow	Q _N = 3,2/8/16/25 l/min
Max. Volume flow	Q _{max} = 25 l/min
Min. Volume flow	Q _{min} = 0,1 l/min
Leakage volume flow	see characteristics
Repeatability	≤ 2 %*
Hysteresis	≤ 5 %*


* at optimal dither signal

CHARACTERISTICS Oil viscosity $\nu = 30 \text{ mm}^2/\text{s}$


Q = f (I) Volume flow adjustment characteristics





Q = f (p) Volume flow pressure characteristics



Q = f (p) Leakage volume flow characteristics



DIMENSIONS/SECTIONAL DRAWINGS

 Cavity drawing acc. to
 ISO 7789-22-01-0-98

 For detailed cavity drawing
 and cavity tools see data
 sheet 2.13-1008

ERSATZTEILLISTE

Position	Article	Description
10	206.2201	EN 175301 Solenoid coil WD37 / 19x50-G24
	206.2200	Solenoid coil WD37 / 19x50-G12
		Junior-Timer
	206.2203	Solenoid coil WJ37 / 19x50-G24
	206.2202	Solenoid coil WJ37 / 19x50-G12
		Deutsch
206.2205		Solenoid coil WG37 / 19x50-G24
	206.2204	Solenoid coil WG37 / 19x50-G12
15	253.8000	HB 4,5 Manual override (data sheet 1.1-300)
	239.2033	HB 0 Plug screw (data sheet 1.1-300)
20	154.2700	Knurled nut
30	160.2187	O-ring ID 18,72x2,62 (NBR)
	160.6187	O-ring ID 18,72x2,62 (FKM)
40	160.2170	O-ring ID 17,17x1,78 (NBR)
	160.6172	O-ring ID 17,17x1,78 (FKM)
50	160.2188	O-ring ID 18,77x1,78 (NBR)
	160.6188	O-ring ID 18,77x1,78 (FKM)
60	160.2156	O-ring ID 15,60x1,78 (NBR)
	160.6156	O-ring ID 15,60x1,78 (FKM)
70	049.3196	Backup ring RD 16,1x19x1,4

ACCESSORIES

Flange and sandwich bodies	Register 2.6
Line mount body	Data sheet 2.9-205
Proportional amplifier	Register 1.13
Mating connector EN 175301-803	Article no. 219.2002

Technical explanation see data sheet 1.0-100